
North America's Leader in Hazardous Material Information Management
1905 Aston Avenue, Carlsbad, CA 92008
Phone (800) 451-8346 Fax (760) 602-8888

MSDS PRODUCT INFORMATION

Date: 10/07/2005
To: MSDS Requester
From: 3E Company
Subject: The MSDS you have requested

☐ MSDS NOT REQUIRED

In response to your request for a Material Safety Data Sheet, according to the OSHA Hazard Communication Standard (Right-to-Know), the following item is an article. Articles are defined in 29 CFR 1910.1200(c). Products such as Drugs, cosmetics, food, or alcoholic beverages, wood or wood products, and tobacco or tobacco products, as defined in 29 CFR 1910.1200(b)(6), are exempt from the Hazard Communication Standard. Items that are considered articles, as defined in 29 CFR 1910.1200(c), are also exempt from this Standard. Therefore, the manufacturer is not required to provide an MSDS for this product.

☐ MSDS DISCONTINUED PRODUCT

In response to your request for a Material Safety Data Sheet, the manufacturer has discontinued the product listed below. The MSDS Attached is the most current version, or an MSDS is no longer available.

☒ MSDS BEST COPY AVAILABLE

The MSDS attached is the best copy available from the manufacturer.

☐ MANUFACTURER NO LONGER IN BUSINESS

In response to your request for a Material Safety Data Sheet, a current MSDS could not be obtained for this product. It has been determined that the manufacturer listed below is no longer in business. A current address and phone number could not be located.

Manufacturer: Behr Process Corporation

Product Name: Behr Premium Plus with Style Pearlescent White Opal No. 751



View Section: 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: **Behr Premium Plus With Style Pearlescent White Opal No. 751**
Product Number: 751
Manufacturer Name: Behr Process Corporation
Address: 3400 W. Segerstrom Avenue
Santa Ana CA 92704

NFPA

U.S. Contact Info.:

Business Phone: (714) 545-7101
Technical Service Phone: (800) 854-0133 ext. 2
Business Fax: (714) 241-1002

1
1 0

HMIS

Canadian Contact Info.:

Business Phone: (800) 661-1591
Technical Service Phone: (800) 661-1591
Business Fax: (800) 387-0019

HEALTH	1
FLAME	0
REACTIVITY	0
PPE	

For Transportation Emergencies:

In the US, call CHEMTREC: (800) 424-9300

In Canada, call CANUTEC: (613) 996-6566 (call collect)

[To Top of page](#)

SECTION 2 : COMPOSITION/INFORMATION ON INGREDIENTS

Product No. 751

Chemical Name	CAS#	Lower Percent	Upper Percent
Acrylic polymer	No data	24.30	25.50
Monoethylene Glycol	107-21-1	13.80	13.80
2,2,4-trimethyl-1,3-pentanediol monoisobutylate	25265-77-4	2.90	2.90
Titanium dioxide	13463-67-7	.30	.30
Non-hazardous ingredients		33.80	34.90

[To Top of page](#)

SECTION 3 : HAZARDS IDENTIFICATION

Product No. 751

Emergency Overview: Irritant.

Applies to all Ingredients:

Potential Health Effects:

Eye Contact: May cause irritation.
Skin Contact: May cause irritation.
Inhalation: Prolonged or excessive inhalation may cause respiratory tract irritation.
Ingestion: May be harmful if swallowed. May cause vomiting.

Chronic Skin Contact:	Prolonged or repeated contact may cause skin irritation.
Target Organs:	Eyes. Skin. Respiratory system. Digestive system.
Signs/Symptoms:	Overexposure may cause headaches and dizziness.
Aggravation of Pre-Existing Conditions:	None generally recognized.
Guideline Type:	No Information Provided

[To Top of page](#)

SECTION 4 : FIRST AID MEASURES

Product No. 751

Eye Contact:	Immediately flush eyes with plenty of water for 15 to 20 minutes. Get medical attention, if irritation or symptoms of overexposure persists.
Skin Contact:	Immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.
Inhalation:	If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.
Ingestion:	If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.
Other First Aid:	Due to possible aspiration into the lungs, DO NOT induce vomiting if Ingested. Provide a glass of water to dilute the material in the stomach. If vomiting occurs naturally, have the person lean forward to reduce the risk of aspiration.

[To Top of page](#)

SECTION 5 : FIRE FIGHTING MEASURES

Product No. 751

Flash Point:	No Data
Upper Flammable or Explosive Limit:	No Data
Lower Flammable or Explosive Limit:	No Data
Extinguishing Media:	Use alcohol foam, carbon dioxide, dry chemical, or water fog or spray when fighting fires involving this material.
Protective Equipment:	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

[To Top of page](#)

SECTION 6 : ACCIDENTAL RELEASE MEASURES

Product No. 751

Personal Precautions:	Use proper personal protective equipment as listed in section 8.
Spill Cleanup Measures:	Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container. Provide ventilation. Clean up spills immediately observing precautions in the protective equipment section.
Environmental Precautions:	Avoid runoff into storm sewers, ditches, and waterways.

[To Top of page](#)

SECTION 7 : HANDLING and STORAGE

Product No. 751

Handling:	Use with adequate ventilation. Avoid breathing vapor and contact with eyes, skin and clothing.
Storage:	Store in a cool, dry, well ventilated area away from sources of heat, combustible materials, and incompatible substances. Keep container tightly closed when not in use.
Hygiene Practices:	Wash thoroughly after handling. Avoid contact with eyes and skin. Avoid inhaling vapor or mist.
Important Storage and Disposal:	DANGER! Rags, steel wool and waste soaked with this product may spontaneously catch fire if improperly discarded or stored. To avoid a spontaneous combustion fire, immediately after use, place rags, steel wool or waste in a sealed, water-filled, metal container. Do not store unused product inside the home. For disposal guidance, contact your household refuse collection service, fire department, county or state government environmental control agency.

[To Top of page](#)

SECTION 8 : EXPOSURE CONTROLS, PERSONAL PROTECTIONProduct No. 751

Engineering Controls:	Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.
Skin Protection Description:	Chemical-resistant gloves and chemical goggles, face-shield and synthetic apron or coveralls should be used to prevent contact with eyes, skin or clothing.
Hand Protection Description:	Wear appropriate protective gloves. Consult glove manufacturer's data for permeability data.
Eye/Face Protection:	Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face protection regulation, or the European standard EN 166.
Respiratory Protection:	A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.
Other Protective:	Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

Ingredient Guidelines**Guideline Type****Guideline Information**

Monoethylene Glycol :

ACGIH TLV-STEL

C 100 mg/m3 (Aerosol only)

Titanium dioxide :

ACGIH TLV-TWA

10 mg/m3

OSHA PEL-TWA

15 mg/m3

[To Top of page](#)

SECTION 9 : PHYSICAL and CHEMICAL PROPERTIESProduct No. 751

Physical State/Appearance:	Liquid
Color:	No information
pH:	8.5 to 9.5
Vapor Density:	Greater than 1 (Air = 1)
Density:	8.4-8.8 Lbs./gal.
Molecular Formula:	Mixture
Molecular Weight:	Mixture

[To Top of page](#)

SECTION 10 : STABILITY and REACTIVITYProduct No. 751

Chemical Stability:	Stable under normal temperatures and pressures.
Conditions to Avoid:	Heat, flames, incompatible materials, and freezing or temperatures below 32 deg. F.
Incompatibilities with Other Materials:	Oxidizing agents. Strong acids and alkalis.
Hazardous Polymerization:	Not reported.
Hazardous Decomposition Products:	Incomplete combustion may produce carbon monoxide and other toxic gases.

[To Top of page](#)

SECTION 11 : TOXICOLOGICAL INFORMATION

Product No. 751

Monoethylene Glycol :

Eye Effect: Eyes - Rabbit : 1440 mg/6H; Moderate.
Eyes - rat: 0.000012%/3D; No effects reported. (RTECS)

Skin Effects: Skin - Rabbit : 555 mg; Mild. (RTECS)
Skin - Rabbit LD50: 9530 uL/kg; Details of toxic effects not reported other than lethal dose value

Titanium dioxide :

Skin Effects: Skin - Human: 300 ug/3D (Intermittent); Mild. (RTECS)

Carcinogenicity: IARC: Group 3: Unclassifiable as to carcinogenicity to humans

[To Top of page](#)

SECTION 12 : ECOLOGICAL INFORMATION

Product No. 751

Ecotoxicity: No ecotoxicity data was found for the product.

Environmental Fate: No environmental information found for this product.

[To Top of page](#)

SECTION 13 : DISPOSAL CONSIDERATIONS

Product No. 751

Waste Disposal: Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local guidelines.

Important Disposal Information: DANGER! Rags, steel wool and waste soaked with this product may spontaneously catch fire if improperly discarded or stored. To avoid a spontaneous combustion fire, immediately after use, place rags, steel wool or waste in a sealed, water-filled, metal container. Do not store unused product inside the home. For disposal guidance, contact your household refuse collection service, fire department, county or state government environmental control agency.

[To Top of page](#)

SECTION 14 : TRANSPORT INFORMATION

Product No. 751

DOT Hazard Class: No Data

DOT Identification Number: No Data

[To Top of page](#)

SECTION 15 : REGULATORY INFORMATION

Product No. 751

2,2,4-trimethyl-1,3-pentanediol monoisobutylate :

TSCA 8(b): Inventory Status: Listed

Monoethylene Glycol :

TSCA 8(b): Inventory Status: Listed

State: Listed in the New Jersey State Right to Know list.

Canada DSL: Listed

Titanium dioxide :

TSCA 8(b): Inventory Status: Listed

Comments: Listed in California Prop65 list

WARNING: This product contains a chemical known to the state of California to cause cancer and birth defects or other reproductive harm.

[To Top of page](#)

SECTION 16 : ADDITIONAL INFORMATION

Product No. 751

MSDS Preparation Date: 5/2003
MSDS Revision Date: 5/2003
MSDS Author: Actio Corporation.

Disclaimer:

This Health and Safety Information is correct to the best of our knowledge and belief at the date of its publication but we cannot accept liability for any loss, injury or damage which may result from its use. We shall ensure, so far as is reasonably practicable, that any revision of this Data Sheet is sent to all customers to whom we have directly supplied this substance, but must point out that it is the responsibility of any intermediate supplier to ensure that such revision is passed to the ultimate user. The information given in the Data Sheet is designed only as a guidance for safe handling, storage and the use of the substance. It is not a specification nor does it guarantee any specific properties. All chemicals should be handled only by competent personnel, within a controlled environment. Should further information be required, this can be obtained through the sales office whose address is at the top of this data sheet.

References:

1. American Chemical Society, STN Easy Online Database
2. Brethericks Reactive Chemical Hazards Database. Version 2.
3. Gassarett and Doulls Toxicology, The Basic Science of Poisons.
4. Hawleys Condensed Chemical Dictionary, Thirteenth Edition
5. IARC monographs on the Evaluation of the Carcinogenic Risk of Chemicals to Man, WHO International Research on Cancer.
6. Industrial Hygiene and Toxicology, by F.A. Patty.
7. National Library of Medicine, Department of Health and Human Services, Hazardous Substances Data Bank (HSDB).
8. National Toxicology Program (NTP) Eighth Report on Carcinogens, 1997.
9. NIOSH Registry of Toxic Effects of Chemical Substances (RTECS) and Pocket Guide to Chemical Hazards.
10. OSHA Hazard Communication Standard, 1910.1200 and Z Tables.
11. Sax Dangerous Properties of Industrial Materials. Tenth Edition.
12. The Merck Index: An Encyclopedia of Chemicals and Drugs. Merck and Company. Twelfth Edition 1998.
13. Threshold Limit Values for Chemical Substances and Physical Agents in the Work Environment and Biological Exposure Indices. TLV Booklet, 2001.

Copyright© 1996-2003 Actio Software Corporation. All Rights Reserved.

The trademarks, service marks, graphics and logos used on this MSDS are registered or unregistered trademarks of BEHR Process Corporation. All Rights Reserved.

To Top of page